

## Round Rods

Grades: Poly Ether Ether Ketone PEEK (NAT/BLK/CNT-R6)

### Dimensions

Diameter (inch)	Tolerance (inch)	Weight (lb)		
		1ft (305mm)	4ft (1219mm)	10ft (3048mm)
0.187	+0.00 ~ +0.035	0.018	0.070	0.176
0.250		0.031	0.123	0.308
0.375	+0.00 ~ +0.04	0.069	0.278	0.694
0.500		0.122	0.487	1.217
0.562		0.154	0.615	1.537
0.625		0.190	0.760	1.901
0.750		0.268	1.072	2.680
0.875	+0.00 ~ +0.06	0.365	1.459	3.648
1.000		0.477	1.905	4.764
1.250		0.740	2.956	7.391
1.375		0.895	3.577	8.943
1.500		1.065	4.257	10.643
1.750		1.450	5.794	14.487
2.000		1.893	7.567	18.922
2.250		2.396	9.578	23.948
2.500	+0.00 ~ +0.08	2.958	11.824	29.565
2.750		3.554	14.204	35.517
3.000		4.230	16.904	42.268
3.250		4.964	19.839	49.606
3.500		5.757	23.009	57.531
4.000	+0.00 ~ +0.15	7.519	30.052	75.142
4.500		9.447	37.759	94.413
4.750		10.526	42.071	105.195
5.000		11.664	46.616	116.559
6.000		16.796	67.127	167.845

- Size range of CNT-R6 is Ø0.187 ~ Ø4.000inch in Length 1ft and Length 4ft only.
- In case of the sizes not specified in above table, please contact us directly.

Sheets & Plates

Grades: Poly Ether Ether Ketone PEEK (NAT/BLK/CNT-R6)

## Dimensions

Thickness (inch)	Tolerance (inch)	Weight (lb)	
		square ft (305mm x 305mm)	2ft x 4ft (609mm x 1219mm)
0.187	+0.00 ~ +0.05	1.471	11.738
0.200		1.573	12.554
0.250		1.966	15.693
0.375		2.891	23.072
0.500	+0.00 ~ +0.06	3.777	30.139
0.625		4.721	37.674
0.750		5.587	44.585
0.875		6.518	52.016
1.000		7.449	59.446
1.125		8.380	66.877
1.250	+0.00 ~ +0.08	9.311	74.308
1.375		10.243	81.739
1.500		11.174	89.169
1.750		12.854	102.576
2.000		14.690	117.230
2.250		16.526	131.884
2.500		+0.00 ~ +0.10	18.362
2.750	20.199		161.191

- Size range of CNT-R6 is Thickness 0.200 ~ 2.000 inch only.
- In case of the sizes not specified in above table, please contact us directly.