

# POM-C



Round Rods

Grades: PolyOxyMethylene (Acetal) POM-C (NAT/BLK/CNT-R6)

## Dimensions

Diameter (inch)	Tolerance (inch)	Weight (lb)			
		1ft (305mm)	3ft (914mm)	5ft (1524mm)	10ft (3048mm)
0.187	+0.00 ~ +0.002	0.02			0.19
0.250		0.03			0.34
0.312		0.05			0.52
0.375		0.07			0.74
0.437		0.10			1.01
0.500		0.13			1.32
0.562		0.16			1.64
0.625		0.20			2.03
0.750		0.29			2.89
0.875		0.39			3.93
1.000	+0.00 ~ +0.005	0.51			5.14
1.125		0.65			6.46
1.250		0.80			7.98
1.375		0.97			9.65
1.500		1.15			11.49
1.625		1.34			13.39
1.750		1.55			15.53
1.875		1.78			17.83
2.000		2.03			20.28
2.125		+0.00 ~ +0.070	2.29		
2.250	2.57				25.67
2.375	2.86				28.60
2.500	3.15				31.48
2.750	3.81				38.09
3.000	4.54				45.33

Continued.

# POM-C



## Round Rods

Grades: PolyOxyMethylene (Acetal) POM-C (NAT/BLK/CNT-R6)

### Dimensions

Diameter (inch)	Tolerance (inch)	Weight (lb)			
		1ft (305mm)	3ft (914mm)	5ft (1524mm)	10ft (3048mm)
3.250	+0.00 ~ +0.125	5.32			53.20
3.500		6.17			61.70
3.750		7.09			70.83
4.000		8.06			80.59
4.250		9.10			90.98
4.500		10.21			101.99
4.750	11.37			113.64	
5.000	+0.00 ~ +0.250	12.60		62.96	125.92
5.500		15.25		76.18	152.36
6.000		18.14		90.66	181.32
6.500		21.29		106.40	212.80
7.000		24.70	74.01	123.40	246.80
8.000		32.26	96.66	161.18	322.35
9.000		40.82	122.34	203.99	407.97
10.000		50.40	151.04	251.84	503.67
11.000		60.98	182.75	304.72	609.44
12.000		72.58	217.49	362.64	725.29

- Size range of CNT-R6 is Ø0.187 ~ Ø4.000inch only.
- In case of the sizes not specified in above table, please contact us directly.

# POM-C



Sheets & Plates

Grades: PolyOxyMethylene (Acetal) POM-C (NAT/BLK/CNT-R6)

## Dimensions

Thickness (inch)	Tolerance (inch)	Weight (lb)			
		square ft (305mm x 305mm)	2ft x 4ft (609mm x 1219mm)	4ft x 8ft (1219mm x 2438mm)	4ft x 10ft (1219mm x 3048mm)
0.250	+0.00 ~ +0.025	2.04	16.32	65.32	81.66
0.312		2.55	20.36	81.52	101.92
0.375		3.03	24.16	96.73	120.93
0.500		4.04	32.22	128.98	161.25
0.625		5.05	40.27	161.22	201.56
0.750		5.98	47.70	190.97	238.75
0.875		6.97	55.65	222.79	278.54
1.000		7.97	63.60	254.62	318.33
1.250	+0.00 ~ +0.05	9.96	79.50	318.28	397.91
1.500		11.88	94.78	379.44	474.37
1.750		13.86	110.58	442.68	553.44
2.000		15.84	126.38	505.92	632.50
2.250		17.82	142.17	569.16	711.56
2.500		19.79	157.97	632.40	790.62
2.750		21.77	173.77	695.64	869.69
3.000		23.75	189.56	758.87	948.75
3.250	+0.00 ~ +0.125	25.73	205.36	822.11	1027.81
3.500		27.53	219.70	879.53	1099.59
3.750		29.50	235.39	942.35	1178.13
4.000		31.46	251.09	1005.18	1256.68
4.500		35.40	282.47	1130.82	1413.76
5.000		39.33	313.86		
6.000		47.19	376.63		

- Size range of CNT-R6 is Thickness 0.250 ~ 2.000inch in square ft and 2ft x 4ft only.
- In case of the sizes not specified in above table, please contact us directly.